

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Trade name : Primary Reference Fuel Octane No. 80
 Product code : HF3004

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Fuel for engine development and testing

1.3. Supplier

Haltermann Solutions™
 15600 W Hardy Rd.
 Houston, TX 77060 - USA
 T 1-800-969-2542 - F 281-457-1469
dphillips@jhaltermann.com

1.4. Emergency telephone number

Emergency number : 24 HR CHEMTREC: 1-800-424-9300; Emergency Assistance: 1-800-969-2542 (8 AM to 5 PM CDT)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapour
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Specific target organ toxicity (single exposure) Category 3	H336	May cause drowsiness or dizziness
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airways
Hazardous to the aquatic environment - Acute Hazard Category 1	H400	Very toxic to aquatic life
Hazardous to the aquatic environment - Chronic Hazard Category 1	H410	Very toxic to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapour
 H304 - May be fatal if swallowed and enters airways
 H315 - Causes skin irritation
 H336 - May cause drowsiness or dizziness
 H400 - Very toxic to aquatic life
 H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, sparks, open flames. - No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/Bond container and receiving equipment
 P241 - Use explosion-proof electrical, lighting, ventilating equipment
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
 P264 - Wash hands thoroughly after handling.

Primary Reference Fuel Octane No. 80

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective clothing, protective gloves.
P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER
P302+P352 - If on skin: Wash with plenty of soap and water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P312 - Call a doctor, a POISON CENTER if you feel unwell
P321 - Specific treatment (see supplemental first aid instruction on this label)
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO₂), dry extinguishing powder, foam to extinguish.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
2,2,4-Trimethylpentane	(CAS-No.) 540-84-1	80
n-Heptane	(CAS-No.) 142-82-5	20

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : Irritation.
Symptoms/effects after ingestion : Risk of lung edema.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.
Reactivity : Highly flammable liquid and vapour.

Primary Reference Fuel Octane No. 80

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2,2,4-Trimethylpentane (540-84-1)		
ACGIH	ACGIH TWA (ppm)	300 ppm
n-Heptane (142-82-5)		
ACGIH	Local name	Heptane, all isomers
ACGIH	ACGIH TWA (ppm)	400 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
ACGIH	Regulatory reference	ACGIH 2018
OSHA	OSHA PEL (TWA) (mg/m ³)	2000 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	500 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA
IDLH	US IDLH (ppm)	750 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	350 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	85 ppm
NIOSH	NIOSH REL (ceiling) (mg/m ³)	1800 mg/m ³

Primary Reference Fuel Octane No. 80

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

n-Heptane (142-82-5)		
NIOSH	NIOSH REL (ceiling) (ppm)	440 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, colorless liquid.
Color	: Colorless
Odor	: gasoline-like
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 96 - 103 °C
Flash point	: -8 °C closed cup
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: 11.7 kPa (1.7 psi) @ 38°C
Relative vapor density at 20 °C	: 3
Relative density	: No data available
Specific gravity / density	: 0.68 g/cm ³
Solubility	: Insoluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: 1 - 7 vol %
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

Primary Reference Fuel Octane No. 80

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

2,2,4-Trimethylpentane (540-84-1)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 14.38 mg/l/4h

n-Heptane (142-82-5)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (mg/l)	103 g/m ³ (Exposure time: 4 h)
ATE US (dermal)	3000 mg/kg body weight
ATE US (vapors)	103 mg/l/4h
ATE US (dust, mist)	103 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : May cause drowsiness or dizziness.

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation.

Symptoms/effects after ingestion : Risk of lung edema.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life with long lasting effects.

2,2,4-Trimethylpentane (540-84-1)	
LC50 fish 1	18.4 mg/l (Oncorhynchus mykiss)
EC50 Daphnia 1	0.4 mg/l

n-Heptane (142-82-5)	
LC50 fish 1	375 mg/l (Exposure time: 96 h - Species: Cichlid fish)
EC50 Daphnia 1	> 10 mg/l 24hr
LC50 fish 2	0.1 mg/l (Exposure time: 96 h - Species: Mysidopsis Bahia)

Primary Reference Fuel Octane No. 80

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

2,2,4-Trimethylpentane (540-84-1)

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

2,2,4-Trimethylpentane (540-84-1)

Bioaccumulative potential	Not established.
---------------------------	------------------

n-Heptane (142-82-5)

Log Pow	4.66
---------	------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

2,2,4-Trimethylpentane (540-84-1)

1990 Hazardous Air Pollutant (Clean Air Act)	Yes
--	-----

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN1268 Petroleum distillates, n.o.s. (Trimethylpentane and Heptane), 3, II
UN-No.(DOT)	: UN1268
Proper Shipping Name (DOT)	: Petroleum distillates, n.o.s. Trimethylpentane and Heptane
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: II - Medium Danger
Hazard labels (DOT)	: 3 - Flammable liquid



Dangerous for the environment	: Yes
Marine pollutant	: Yes



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242

Primary Reference Fuel Octane No. 80

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: 144 - If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 280.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see 171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F). TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
Emergency Response Guide (ERG) Number	: 128
Other information	: No supplementary information available.

Transport by sea

Transport document description (IMDG)	: UN 1268 PETROLEUM DISTILLATES, N.O.S. (Trimethylpentane and Heptane), 3, II
UN-No. (IMDG)	: 1268
Proper Shipping Name (IMDG)	: PETROLEUM DISTILLATES, N.O.S.
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger
Limited quantities (IMDG)	: 1 L
Marine pollutant	: Yes



Air transport

Transport document description (IATA)	: UN 1268 Petroleum distillates, n.o.s. (Trimethylpentane and Heptane), 3, II
UN-No. (IATA)	: 1268
Proper Shipping Name (IATA)	: Petroleum distillates, n.o.s.
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Primary Reference Fuel Octane No. 80

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,2,4-Trimethylpentane (540-84-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

CERCLA RQ

1000 lb

n-Heptane (142-82-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

2,2,4-Trimethylpentane (540-84-1)

Listed on the Canadian DSL (Domestic Substances List)

n-Heptane (142-82-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

2,2,4-Trimethylpentane (540-84-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

n-Heptane (142-82-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

2,2,4-Trimethylpentane (540-84-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

n-Heptane (142-82-5)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

2,2,4-Trimethylpentane (540-84-1)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

n-Heptane (142-82-5)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date

: 06/19/2018

Primary Reference Fuel Octane No. 80

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

NFPA health hazard


: 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



SDS US (GHS HazCom 2012)

This information is furnished without warranty, expressed or implied except that it is accurate to the best knowledge of Haltermann Solutions™. The data on this sheet are related only to the specific material herein. Haltermann Solutions™ assumes no responsibility for the use or reliance upon these data.