

## *Poly-G*<sup>®</sup> 83-170

*Poly-G*®\* 83-170 polyol is a hetero polyol that contains unusually high ethylene oxide content, imparting good hydrophilic properties to products made with it. It has been used in applications ranging from soft elastomeres to sponge-like flexible foams.

A glycereol –based triol, Poly-G 83-170 polyol has a nominal molecular weight of 1000. It is a stable, practically colorless liquid that is neither volatile nor corrosive, with a low pour point and high flash point.<sup>1</sup>

Typical physical properties are presented in Table 1.

170
0.05
0.05
70 max.
6
Clear & substantially
free of suspended matter
185
1.10
>149
>300

## Storage and Handling

*Poly-G* 83-170 polyol should be stored in a cool, dry area. To prevent moisture absorption, this product may be stored under an atmosphere of dry nitrogen.

*Poly-G* 83-170 polyol should not come in contact with strong oxidizers.

## For More Information Technical Service

Technical service is available to facilitate further use of Monument Chemical products. If you have a specific question or need further information, please write or call Monument Chemical, Customer Service, 2450 Olin Road, Brandenburg, KY 40108; (800) 636-3786, or fax: (270) 422-6456.

Or visit our web site at: www.monumentchemical.com

## How To Order

To place orders for delivery in the U.S. or Canada and to get fast answers on order status or product availabilities, call our toll-free number: (800) 636-3786.

For written inquiries about orders, and to place confirmations, send to Monument Chemical, Customer Service, 2450 Olin Road, Brandenburg, KY 40108.

<sup>&</sup>lt;sup>1</sup>The flammability properties of this material, or any other material, are not intended to reflect the fire hazards presented by any resultant cellular or foamed plastic product.

<sup>\*</sup>*Poly-G*<sup>®</sup> is a registered trademark of Monument Chemical Kentucky LLC.



Please refer to the Material Safety Data Sheet (MSDS) for complete information on Storage and Handling, Toxicological Properties, Personal Protection, First Aid, Spill and Leak Procedures, and Waste Disposal. To order an MSDS, call Monument Chemical at (800) 636-3786. Before using or handling this product, the MSDS should be thoroughly reviewed.

This bulletin and the information contained herein are offered solely for your consideration, investigation and verification. NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, OF MERCHANTABILITY OR OTHERWISE, ARE MADE OR CONTAINED HEREIN. Monument Chemical's exclusive responsibility for any claims, including claims based on negligence, arising in connection with the information contained herein or the subsequent purchase, use, storage or handling of the product will in no event exceed Monument Chemical's sales price for the product with respect to which damages are claimed. IN NO EVENT WILL MONUMENT CHEMICAL BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. User accepts full responsibility for compliance with all applicable Federal, state and local laws and regulations. Nothing contained herein will be construed to constitute permission or a recommendation to use the product in any process or formulation covered by a patent or a patent application owned by Monument Chemical or by others. No statements or representations which differ from the above shall be binding upon Monument Chemical unless contained in a duly executed written agreement.